VAISALA

TMW110
Wall mount Temperature Transmitter



TMW110 Order Form
G010039EN-B
Valid from February 2024

					1	2	3	4	5	6	7	8
	Wall mount Temperature Transmitter			**TMW110**			**N**	**V**	**0**			
settings	1 Output Signals		**4...20 mA 2-wire loop-powered**		**2**							
	and display	•	*4...20 mA 2-wire loop-powered, with display*		*4*							
			Modbus RTU		**M**							
		•	*Modbus RTU, with display*		*N*							
	2 Measured Parameter for Channel 1		**T 0 ... +50°C (32 ... 122 °F)**			**1**						
	and display [1]		**T -5 ... +55°C (23 ... 131 °F)**			**2**						
			T -40 ... +60°C (-40 ... 140 °F)			**3**						
			T special scale °C, please specify:	_____		**X**						
			T special scale °F, please specify:	_____		**Y**						
			No selection (Modbus model) [2]			**N**	**N**	**V**	**0**			
acc.	6 User guide		**No User's Guide**							**0**		
		•	*Multilingual Quick Guide for HMDW110 Series*							*1*		
hardware	7 Display options		**Metric Units**								**1**	
			Non-Metric Units								**2**	
			Metric units only (cannot be changed after delivery)								**3**	
			No display								**N**	
	8 Other options		**No selection**									**N**
			M12 connector instead of cable gland									**B**

1) Selects output parameter for analog output and the display (in devices with display)
2) Choose No selection (Modbus model) for Modbus devices without display

NOTE:
- **Selections in bold are included in the prices of the basic versions.**
- *Selections in italic are available at an extra price.*
- \+ Suggested/default selection

LINKS:
User Guides
Datasheet
Vaisala.com product page

Example of order code with typical settings:

		1	2	3	4	5	6	7	8
Loop powered:	**TMW110**	**2**	**3**	**N**	**V**	**0**	**0**	**N**	**N**
Loop powered, display:	**TMW110**	*4*	**3**	**N**	**V**	**0**	**0**	**1**	**N**
Modbus,no display:	**TMW110**	**M**	**N**	**N**	**V**	**0**	**0**	**N**	**B**
Modbus,display:	**TMW110**	*N*	**3**	**N**	**V**	**0**	**0**	**1**	**B**

Accessories and spare parts

Conduit Fitting + O-Rin M16x1.5 / PG9, RE-MS	210674SP
Conduit Fitting + O-Rin M16x1.5 / NPTI/2 Inch	210675SP
USB Service Cable M8-4F, RS485	219690
MI70 Connection Cable with M8-4F Connector	219980SP
Terminal Block, Blue PK1304D 4P	236620SP
Membrane Filter PC White UV stabilized	ASM210856SP
Porous PTFE Filter Ø12, L22mm	DRW239993SP